

PDU20MVHVIEC24F

### ENTRY-LEVEL POWER DISTRIBUTION WITH LED PANEL

#### Provides reliable power distribution with real-time load monitoring for connected equipment

Ideal for server room and data center applications, the Metered PDU Series is a power distribution device that delivers electricity from a single source to multiple devices. The PDUs' built-in LED panel can clearly show the real-time load monitoring in amps. The products also feature overload protection, external site ground pin, industrial-grade metal housing, adjustable mounting brackets, long input power cord, and cord retention tray.

#### APPLICATION


- Office
- Server room
- Factory
- Surveillance systems
- Networking devices
- Satellite devices
- Workstations
- Back office
- Data center
- Security systems
- Telecom devices
- NAS/Storage devices
- Multimedia devices

#### SERIES FEATURES

- Real-Time Local Monitoring
- Cord Retention Tray
- Industrial-grade Metal Housing
- Adjustable Mounting Brackets

#### PRODUCT CALLOUTS

1. AC Inlet
2. Output Circuit Breaker
3. Ground Stud
4. AC Outlets
5. Meter Readout
6. Cord Retention Tray Screw Holes



PDU20MVHVIEC24F

#### TECHNICAL SPECIFICATIONS

Model Name	PDU20MVHVIEC24F
<b>Input</b>	
Nominal Input Voltage (Vac)	200 - 240
Input Frequency (Hz)	50 / 60
Maximum Input Current (A)	16
Input Connector Type	IEC C20 x 1
Power Cord Length (m.)	3.05
<b>Output</b>	
Over Current Protection (Each Bank) (A)	16
Outlets - # of Bank(s) (Bank)	1
Outlet(s) - Total	24
Outlet(s) - Front	24
Outlet Type	IEC C13 x 20, IEC C19 x 4
<b>Management &amp; Communications</b>	
LED Indicators	Load
<b>Physical</b>	
Installed Rack Height (U)	0
Cord Retention Tray	Yes
<b>Physical Size</b>	
Dimensions (WxHxD) (mm.)	44.45 x 1219.2 x 38.1
Weight (kg.)	2.63
<b>Environmental</b>	
Operating Temperature (°C)	0 - 35
Operating Relative Humidity (Non-condensing) (%)	0 - 95
<b>Certifications</b>	
Certifications	CE, UL60950
RoHS	Yes

#All specifications are subject to change without notice.

